

DATASHEET

tempmate.®-XS

The affordable single-use temperature datalogger






MAIN TECHNICAL SPECIFICATIONS tempmate.®-XS

Usage Type	Single-Use
Monitored Information	Temperature
Dimension [mm]	48 mm x 30 mm x9 mm (L x W x H)
Weight [g]	8.6g
Casing	PE+PET
Battery	CR2023 / non replaceable
Temperature Range	-10 °C to +70 °C (possible down to -20 °C with limited run time)
Temperature Accuracy	±0.5 °C (-10 °C to +40 °C) ±1.0 °C (others)
Temperature Resolution	0.1 °C
T90	5 min (internal sensor)
Indication / Display	LED indication
Protection Class	IP67
Shelf Life	Minimum 12 months*
Connection Interface	USB 2.0, A-Type
Memory Capacity (measurements)	10,000 points
Run Time	Up to 70 days (depending on temperature range & log interval)
Logging Interval	Default: 10 min.; others on request
Startup Mode	Button, start through tempbase 2 Software
Stop Mode	Button or through tempbase 2 Software
Alarm Configuration	Up to 2 alarm limits customizable, single or cumulative via tempbase 2 Software

OTHER SPECIFICATIONS

Temporary PDF	The PDF Report is available at anytime without stopping the Logger
Conformity	EN 12830, CE, RoHS, RTC-DO-160, MSDS
Validation Certificate	6 points (hardcopy) & PDF in memory
Reprogrammable	Yes, via tempbase 2 Software
Report Generation	Automatic PDF summary report, full report through tempbase 2 Software
Password Protection	Optional on request
Backup-Log-Feature	Yes
Accessories incl.	Validation Certificate, Sealed Zip-Bag

* Since environmental influences can affect the lifespan of batteries, we recommend that all our products be stored in the conditions that are optimal for them. In this way, the shelf life given at the time of purchase can be guaranteed.
Optimal storage conditions: +15°C to +23°C / 45% to 75% rH.



Consumibles de Seguridad, S.L.
Paseo de la Castellana, 91 - 4º 1ª
28046 MADRID

+34 630 32 42 43

info@consumiblesdeseguridad.com

www.consumiblesdeseguridad.com

PLEASE, contact us for further questions.